



2330 G3 M73 PW19 3600-830 ETWD

Recessed LED luminaire

TOC: 7631865



Product description

Luminaire type

Square recessed LED ceiling luminaire with prismatic PMMA cover. Version M73 (600 mm x 600mm).

Light management

Suitable for control via smartphone/tablet with LiveLink Basic Wireless app (iOS and Android).

Applications

Offices, Corridors, Foyers, Conference rooms, Retail areas, waiting zones.

Mounting methods

For system ceilings with exposed grids.

Optical system

PMMA cover with microprisms. With symmetric limited wide light distribution. beam angle 81°. Glare evaluation according to UGR rating (EN 12464-1) < 19. Suitable for VDU workstations according to EN 12464-1 via limited luminance $L \leq 3000 \text{ cd/m}^2$ for beam angle above 65° all-round. Harmonious light effect due to homogeneously illuminated light emission.

LED system

Luminaire luminous flux and light color fixed. Luminaire luminous flux 3400 lm, connected load 31 W, Power Faktor $\lambda > 0,95$, maximum luminous efficiency of luminaire 110 lm/W. Light colour warm white, correlated colour temperature (CCT) 3000 K, general colour rendering index (CRI) $R_a > 80$. Colour locus tolerance (initial MacAdam) $\leq 4 \text{ SDCM}$. Mean rated service life $L70 (t_q 25^\circ\text{C}) = 50,000 \text{ h}$.

Luminaire body

Luminaire body of aluminium. Surface coated white (similar to RAL 9016). Dimensions (L x W): 595 mm x 595 mm, luminaire height 65 mm. Safety class (EN 61140): II, protection rating (DIN EN 60529): IP20, Protection rating on room side: IP40, impact resistance level in accordance with IEC 62262: IK02, testing temperature of wire glow test in accordance with IEC 60695-2-11: 650 °C. Permissible ambient temperature (t_a): 25 °C. Weight: 2,2 kg.

Electrical version

With electronic control gear unit, dimmable (radio). The control gear unit is replaceable in accordance with the ecodesign requirements (VO (EU) 2019/2020). Light can be switched and dimmed using a wireless push-button. The luminaire complies with the fundamental requirements of applicable EU regulations and product safety legislation and bears the CE symbol. The luminaire is also ENEC-certified by an independent testing authority.

Disassembly instructions (PDF) for the product available at: <https://www.trilux.com/EcoDesign>

Product features and key data

Applications	Offices Corridors Foyers Conference rooms Sales rooms Waiting zones
Luminaire type	Square recessed LED ceiling luminaire with prismatic PMMA cover.
Mounting method	Recessed
Luminaire optic	PMMA cover with microprisms.
Light distribution curve	Wide reduced glare UGR19 (W19)
FWHM	80,60 °
Light Engine	standard product
Colour temperature	3000 K

Product features and key data

Rated luminous flux	3400 lm
Connected load	31,00 W
Luminous efficacy	110 lm/W
Rated service life	L70 (25 °C) = 50.000 h
Colour rendering index	80
Colour tolerance	4 SDCM
Photobiological class	Group 0 - no risk
Luminaire colour	RAL9016 Traffic white
Luminaire body	Luminaire body of aluminium.
Electrical version	With electronic control gear unit, dimmable (radio).
Wire diameter	1,50 mm²
Connection method	Plug-in terminal
Dimming range	1 - 100 %
Mains voltage	220 - 240 V
Mains frequency	50/60 Hz
Total harmonic distortion < %	14 %
Ingress Protection (IP) rating	IP20
Protection rating on room side	IP40
Protection class	II
Impact resistance (IK)	IK02
Hot wire resistance	650 °C
Ambient temperature	25 °C
Max. Luminaires B10	31
Max. Luminaires B16	50
Max. Luminaires C10	52
Max. Luminaires C16	85
Net length	595 mm
Net width	595 mm
Net height	65 mm
Recess length	595 mm
Recess width	595 mm
Recess depth	190 mm
Weight	2,2 kg

Available accessories

Material	Description
7918300	

EPREL - European Product Registry for Energy Labelling

Energy Efficiency Class

D

Model identifier

S10229194A

For more sustainability in day-to-day business

New
packing



CO₂ OPTIMISED



NO PLASTIC



ONLY ONE MATERIAL



100% RECYCLABLE



www.trilux-twenty3.com/eco