




# 2340 G2 WD2 LED 22/16/ML-8MC ET

## LED wall and ceiling luminaire

TOC: 7790340



## Product description

### Luminaire type

Round surface-mounted LED luminaire with polystyrene diffuser.

### Applications

For entrance areas, corridors, stairways, lounges, hotels, restaurants and residential zones.

### Mounting methods

For wall or ceiling mounting. Secure diffuser fixing with bayonet fixing mechanism.

### Optical system

Round, opal diffuser, spherical construction. With Lambertian light distribution.

### LED system

Luminaire luminous flux adjustable in 3 levels (Multilumen). Luminaire luminous flux 800 lm - 2200 lm, connected load 7,00 W - 18,00 W, maximum luminous efficiency of luminaire 122.22 lm/W. Light colour neutral white, correlated colour temperature (CCT) 4000 K, general colour rendering index (CRI)  $R_a > 80$ . Colour locus tolerance (initial MacAdam)  $\leq 5$  SDCM. The light source is replaceable according to the ecodesign requirements (VO (EU) 2019/2020).

### Luminaire body

Luminaire body of aluminium. Surface coated white (similar to RAL 9016). Diameter of diffuser  $\varnothing 400$  mm, luminaire height 88 mm. Safety class (EN 61140): I, protection rating (DIN EN 60529): IP20, impact resistance level in accordance with IEC 62262: IK02, testing temperature of wire glow test in accordance with IEC 60695-2-11: 650 °C. Permissible ambient temperature ( $t_a$ ): 25 °C Weight: 0,9 kg.

### Electrical version

With electronic transformer, switchable. The control gear unit is replaceable in accordance with the ecodesign requirements (VO (EU) 2019/2020). The luminaire complies with the fundamental requirements of applicable EU regulations and product safety legislation and bears the CE symbol. The luminaire is also ENEC-certified by an independent testing authority.

## Product features and key data

<b>Applications</b>	Entrance areas Corridors Stairways Recreation rooms Hotels and restaurants Residential areas	
<b>Luminaire type</b>	Round surface-mounted LED luminaire with polystyrene diffuser.	
<b>Mounting method</b>	Surface-mounting	
<b>Luminaire optic</b>	Round, opal diffuser, spherical construction.	
<b>Light distribution curve</b>	Lambertian (L)	
<b>FWHM</b>	122,60 °	
<b>Light Engine</b>	Level 3	Level 2
<b>Colour temperature</b>	3000 K	4000 K
<b>Rated luminous flux</b>	1500 lm	2200 lm
<b>Connected load</b>	14,00 W	20,00 W
<b>Luminous efficacy</b>	107 lm/W	110 lm/W
<b>Rated service life</b>	L70 (25 °C) = 50.000 h	
<b>Colour rendering index</b>	80	
<b>Colour tolerance</b>	5 SDCM	

## Product features and key data

Photobiological class	Group 0 - no risk
Luminaire colour	RAL9016 Traffic white
Luminaire body	Luminaire body of aluminium.
Electrical version	With electronic transformer, switchable.
Wire diameter	1,50 mm²
Connection method	Plug-in terminal
Mains voltage	220 - 240 V
Mains frequency	50/60 Hz
Total harmonic distortion < %	14 %
Ingress Protection (IP) rating	IP20
Protection class	I
Impact resistance (IK)	IK02
Hot wire resistance	650 °C
Ambient temperature	25 °C
Max. Luminaires B10	14
Max. Luminaires B16	22
Max. Luminaires C10	23
Max. Luminaires C16	38
Net height	88 mm
Outside diameter	400 mm
Weight	0,9 kg

## Light Engine Data

Light Engine	Color temperature	Rated light current	Power supply value Typ	Luminous efficacy
Level 3	3000 K	1500 lm	14,00 W	107 lm/W
Level 4	3000 K	2100 lm	20,00 W	105 lm/W
Level 1	4000 K	1600 lm	14,00 W	114 lm/W
Level 2	4000 K	2200 lm	20,00 W	110 lm/W

## EPREL - European Product Registry for Energy Labelling

Energy Efficiency Class	Model identifier
D	MCL-D400-19W G1

## For more sustainability in day-to-day business

New  
packing



CO<sub>2</sub> OPTIMISED



NO PLASTIC



ONLY ONE MATERIAL



100% RECYCLABLE



[www.trilux-twenty3.com/eco](http://www.trilux-twenty3.com/eco)