



# 2325 G3 C07 S OA LED 20/14/08/ML-840 ET

## Planar LED downlight

TOC: 7791040



## Product description

### Luminaire type

LED downlight for ceilings with cavity dimensions  $\geq 50$  mm.

### Mounting methods

Tool-free ceiling installation via rapid-mounting springs. Cut-out opening  $\varnothing 200$  mm, Recess depth 43 mm.

### Optical system

With opal PMMA cover. With Lambertian light distribution.

### LED system

Luminaire luminous flux adjustable in 3 levels. Luminaire luminous flux 800 lm - 1800 lm, connected load 7.5 W - 16.5 W, Power Factor  $\lambda > 0,9$ , maximum luminous efficiency of luminaire 122 lm/W. Light colour neutral white, correlated colour temperature (CCT) 4000 K, general colour rendering index (CRI)  $R_a > 80$ . Colour locus tolerance (initial MacAdam)  $\leq 4$  SDCM. The light source is replaceable according to the ecodesign requirements (VO (EU) 2019/2020).

### Luminaire body

Luminaire body of PC. Ceiling ring powder-coated white (similar to RAL 9016). External dimensions of ceiling ring  $\varnothing 230$  mm, luminaire height 43 mm. Permissible ambient temperature ( $t_a$ ): 25 °C to +. Safety class (EN 61140): I, protection rating (DIN EN 60529): IP20, impact resistance level in accordance with IEC 62262: IK02, testing temperature of wire glow test in accordance with IEC 60695-2-11: 650 °C. Weight: 0,5 kg.

### Electrical version

With electronic control gear unit, switchable. The control gear unit is replaceable in accordance with the ecodesign requirements (VO (EU) 2019/2020). The luminaire complies with the fundamental requirements of applicable EU regulations and product safety legislation and bears the CE symbol. The luminaire is also ENEC-certified by an independent testing authority.

### Sustainability

Environmental Product Declaration in accordance with ISO 14025:2006 and EN 15804:2012+A2:2019/AC:2021 and verified carbon offset.

Disassembly instructions (PDF) for the product available at: <https://www.trilux.com/EcoDesign>

## Product features and key data

<b>Luminaire type</b>	LED downlight for ceilings with cavity dimensions $\geq 50$ mm.	
<b>Luminaire optic</b>	With opal PMMA cover.	
<b>Light distribution curve</b>	Lambertian (L)	
<b>FWHM</b>	113,40 °	
<b>Light Engine</b>	Level 1	Level 3
<b>Colour temperature</b>	4000 K	4000 K
<b>Rated luminous flux</b>	800 lm	1800 lm
<b>Connected load</b>	7,50 W	16,50 W
<b>Luminous efficacy</b>	107 lm/W	109 lm/W
<b>Colour rendering index</b>	80	
<b>Colour tolerance</b>	4 SDCM	
<b>Photobiological class</b>	Group 0 - no risk	

## Product features and key data

Luminaire colour	RAL9016 Traffic white
Luminaire body	Luminaire body of PC.
Electrical version	With electronic control gear unit, switchable.
Connection method	Plug-in terminal
Mains voltage	220 - 240 V
Mains frequency	50/60 Hz
Total harmonic distortion < %	14 %
Ingress Protection (IP) rating	IP20
Protection rating on room side	IP44
Protection class	I
Impact resistance (IK)	IK02
Hot wire resistance	650 °C
Ambient temperature	25 °C
Max. Luminaires B10	16
Max. Luminaires B16	25
Max. Luminaires C10	26
Max. Luminaires C16	42
Net height	43 mm
Outside diameter	230 mm
Recess depth	43 mm
Weight	0,5 kg
Recessing diameter	200 mm

## Available accessories

Material	Description
8120500	Refurbishment plate 2325 G3 C07... . For ceiling cut-outs Ø 220 -250 mm.

## Light Engine Data

Light Engine	Color temperature	Rated light current	Power supply value Typ	Luminous efficacy
Level 1	4000 K	800 lm	7,50 W	107 lm/W
Level 2	4000 K	1400 lm	11,50 W	122 lm/W
Level 3	4000 K	1800 lm	16,50 W	109 lm/W

## EPREL - European Product Registry for Energy Labelling

Energy Efficiency Class

Model identifier

D

MDL-D140-14.1W G1

## For more sustainability in day-to-day business

New  
packing



CO<sub>2</sub> OPTIMISED



NO PLASTIC



ONLY ONE MATERIAL



100% RECYCLABLE



[www.trilux-twenty3.com/eco](http://www.trilux-twenty3.com/eco)