






























### Product features and key data

Luminaire colour	RAL9005 Jet black
Ingress Protection (IP) rating	IP20
Protection class	I
Net length	2.000 mm
Net width	31 mm
Net height	38 mm
Weight	1,9 kg

### Available accessories

Material	Description
 <b>Rail Endk D 3PH ST 9004/B 05</b> 8880400	End cap for covering front ends of 3-phase surface-mounted track. Colour black (similar to RAL 9005).
 <b>Rail Haken 3PH ST S-9000/H-B 05</b> 8881000	Universal hook for suspended ceiling mounting. Colour black (similar to RAL 9005)..
 <b>Rail Blind D/C/H 3PH ST S-9000/GP-B 05</b> 8881200	Blank cover for the 3-phase track system Rail. Colour black (similar to RAL 9005). Dimensions (L x W x H): 1000 mm x 11 mm x 26 mm.
 <b>Rail Schneidewerkzeug 3PH ST S-9000/T</b> 8881400	Tool for shortening the track copper conductors.
 <b>Rail Verschlussk 3PH ST S-9000/TP-G 03</b> 8881500	Sealing cap for covering rail grooves. Colour silver gray (similar to RAL 9006).
 <b>Rail Einsp-R D/C/CT 3PH ST 9001/B 05</b> 8881600	Feed for 3-circuit track with DALI equipment. Colour black (similar to RAL 9005).
 <b>Rail Einsp-L D/C/CT 3PH ST 9002/B 05</b> 8881800	Feed for 3-circuit track with DALI equipment. Colour black (similar to RAL 9005).
 <b>Rail I-Verb D/C 3PH ST 9010/B 05</b> 8882000	I-connector for mechanical and electrical connection of two 3-circuit track segments with DALI equipment. With infeed option. With feed-in device for centre feed. Colour black (similar to RAL 9005).
 <b>Rail Längsver D/C 3PH ST9003/B 05</b> 8882200	Conductive coupling without feed-in device for integrated mechanical and electrical connection. Colour black (similar to RAL 9005).
 <b>Rail LängsverNL D/C ST9003/B-M 05</b> 8882400	Non-conductive coupling without feed-in device for integrated mechanical connection. Colour black (similar to RAL 9005).

	<b>Rail L-Verb-L D/C/CT 3PH ST 9011/B 05</b> 8882600	L-connector for two 3-circuit track segments with DALI equipment. With infeed option. Colour black (similar to RAL 9005).
	<b>Rail L-Verb-R D/C/CT 3PH ST 9012/B 05</b> 8882800	L-connector for two 3-circuit track segments with DALI equipment. With infeed option. Colour black (similar to RAL 9005).
	<b>Rail T-Verb-L D/C 3PH ST 9013/B 05</b> 8883000	T-connector for three 3-circuit track segments with DALI equipment. With infeed option. Colour black (similar to RAL 9005).
	<b>Rail T-Verb-L D/C 3PH ST 9015/B 05</b> 8883200	T-connector for three 3-circuit track segments with DALI equipment. With infeed option. Colour black (similar to RAL 9005).
	<b>Rail T-Verb-R D/C 3PH ST 9014/B 05</b> 8883400	T-connector for three 3-circuit track segments with DALI equipment. With infeed option. Colour black (similar to RAL 9005).
	<b>Rail T-Verb-R D/C 3PH ST 9016/B 05</b> 8883600	T-connector for three 3-circuit track segments with DALI equipment. With infeed option. Colour black (similar to RAL 9005).
	<b>Rail X-Verb D/C 3PH ST 9017/B 05</b> 8883800	X-connector for four 3-circuit track segments with DALI equipment. With infeed option. Colour black (similar to RAL 9005).
	<b>Rail Flex-Verb D 3PH ST 9018/B 05</b> 8884000	Flexible connector for two 3-circuit track segments with DALI equipment. Colour black (similar to RAL 9005).
	<b>Rail Clip D STS-9000/115-B 05</b> 8888600	Fixing clip for direct ceiling surface-mounting. Colour black (similar to RAL 9005).
	<b>Rail ZS D/15 3PH ST 9000-KIT8-1,5-B 05</b> 8888800	Wire suspension for suspension lengths to: 1500 mm. Colour black (similar to RAL 9005).
	<b>Rail ZS D/30 3PH ST 9000-KIT8-3-B 05</b> 8889000	Wire suspension for suspension lengths to: 3000 mm. Colour black (similar to RAL 9005).
	<b>Rail ZS-S D/12 3PH ST9000-KIT27-B 05</b> 8898800	Pendant suspension for suspension lengths to: 1200 mm. Colour black (similar to RAL 9005).
	<b>Rail Längsver D/15 ST9000-KIT28-1,5-B 05</b> 8899800	Connection set consisting of one connection bracket and one conductive coupling without feed-in device for integrated mechanical and electrical connection. Wire suspension set consists of one galvanised steel wire Ø 1.5 mm, fixing clip and decorative sleeve made of stainless steel. Colour black (similar to RAL 9005).
	<b>Rail Längsver D/30 ST9000-KIT28-3-B 05</b> 8900000	Connection set consisting of one connection bracket and one conductive coupling without feed-in device for integrated mechanical and electrical connection. Wire suspension set consists of one galvanised steel wire Ø 1.5 mm, fixing clip and decorative sleeve made of stainless steel. Colour black (similar to RAL 9005).
	<b>Rail Clip D T-Sch STS-9000/119-TB-B 05</b> 8900700	Track clip with spring clip for fastening track to Odenwald ceilings. Reutlinger system. Packaging unit has 1 piece. Colour black (similar to RAL 9005).
	<b>Rail Längsver D/C ST9000-KIT35-B 05</b> 8913100	Connection set consisting of one connection bracket and one conductive coupling without feed-in device for integrated mechanical and electrical connection. Colour black (similar to RAL 9005).
	<b>Rail Deckenbef D STS-9000/131-B 05</b> 9242900	Ceiling mounting element with slotted hole recesses to accommodate the fastening hardware and fix to the track. Colour black (similar to RAL 9005).
	<b>Rail Adapter ZZT/515/1800 ST9999/B 05/05</b> 6000659251	Stromschienenadapter mit Textilleitung für das Abhängen von Leuchten am 3-Phasen-Stromschienensystem (DALI) Rail. Cable length: 1800 mm. Maximum Load Value: 5 kg. Bei einem Lastwert > 5 kg ist eine zusätzliche Seilabhängung der Stromschiene zwingend erforderlich. Farbe des Stromschienenadapters black (similar to RAL 9005). Colour of textile cable black (similar to RAL 9005).
	<b>Rail Adapter ZZT/515/2000 ST9999/B 05/11</b> 6000659451	Stromschienenadapter mit transparenter Zuleitung für das Abhängen von Leuchten am 3-Phasen-Stromschienensystem (DALI) Rail. Cable length: 2000 mm. Maximum Load Value: 5 kg. Bei einem Lastwert > 5 kg ist eine zusätzliche Seilabhängung der Stromschiene zwingend erforderlich. Farbe des Stromschienenadapters black (similar to RAL 9005).



**ZAE/05 515**  
7853800

Ceiling rose for connection of the 5-pole mains cable in case of ceiling outlets. Square, black.



**ZAA/05**  
7797800

Ceiling rose, round. Colour black.



**ZAR/05**  
7853900

Ceiling rose, square, black.



**ZAR+LLWC 05**  
7854000

Ceiling rose, square, black. With integrated light management component: LiveLink WLAN-Controller.

#### Offer text

3-circuit surface-mounted track with DALI equipment (6 conductors). System Rail (Stucchi). Also suitable for suspended mounting with accessories to be ordered separately. Made of aluminium, powder-coated. With fine surface structure. Colour black (similar to RAL 9005). Dimensions (L x W x H): 2000 mm x 31 mm x 38 mm.

In combination with track connectors, individual decorative lines for architectural lighting can be realised. The polarity of the neutral conductor must be observed during planning.