



2360 G2 H2 PW19-IL 6000-8MC ETDD

TOC: 8909351



Product description

Luminaire type

LED suspended luminaire with translucent PMMA cover. Suspended luminaire for single luminaire applications.

Mounting methods

Y wire suspension for suspension lengths to: 1780 mm. Y-wire suspension and electric connection cable included in scope of supply.

Optical system

With symmetric limited wide light distribution. Glare evaluation according to UGR rating (EN 12464-1) < 19. Suitable for VDU workstations according to EN 12464-1 via limited luminance $L \leq 3000 \text{ cd/m}^2$ for beam angle above 65° all-round.

LED system

Luminaire luminous flux adjustable in 2 steps. Luminaire luminous flux 5600 lm, connected load 46 W, maximum luminous efficiency of luminaire 130 lm/W. Light colour warm white or neutral white, correlated colour temperature (CCT) 3000 K or 4000 K, general colour rendering index (CRI) $R_a > 80$. Colour locus tolerance (initial MacAdam) $\leq 3 \text{ SDCM}$. Mean rated service life $L65(t_q 25^\circ\text{C}) = 50,000 \text{ h}$.

Luminaire body

Luminaire body of extruded aluminium profile. Surface coated white (RAL 9016). Dimensions (L x W): 1500 mm x 300 mm, luminaire height 20 mm. Safety class (EN 61140): I, protection rating (DIN EN 60529): IP20, impact resistance level in accordance with IEC 62262: IK02, testing temperature of wire glow test in accordance with IEC 60695-2-11: 650 °C. Weight: 6,0 kg.

Electrical version

The control gear unit is replaceable in accordance with the ecodesign requirements (VO (EU) 2019/2020). The luminaire complies with the fundamental requirements of applicable EU regulations and product safety legislation and bears the CE symbol. The luminaire is also ENEC-certified by an independent testing authority.

Disassembly instructions (PDF) for the product available at: <https://www.trilux.com/EcoDesign>

Product features and key data

Luminaire type	LED suspended luminaire with translucent PMMA cover.	
Mounting method	Suspension	
Light Engine	Level 1	Level 2
Colour temperature	3000 K	4000 K
Rated luminous flux	5600 lm	6000 lm
Connected load	46,00 W	46,00 W
Luminous efficacy	122 lm/W	130 lm/W
Service life	L65 (25 °C) = 50.000 h	
Colour rendering index	80	
Colour tolerance	3 SDCM	
Photobiological class	Group 0 - no risk	
Luminaire colour	RAL9016 Traffic white	
Luminaire body	Luminaire body of extruded aluminium profile.	
Connection method	Plug-in terminal	

Product features and key data

Mains voltage	220 - 240 V
Mains frequency	50/60 Hz
Total harmonic distortion < %	14 %
Ingress Protection (IP) rating	IP20
Protection rating on room side	IP20
Protection class	I
Impact resistance (IK)	IK02
Hot wire resistance	650 °C
Ambient temperature	25 °C
Max. Luminaires B10	7
Max. Luminaires B16	12
Max. Luminaires C10	12
Max. Luminaires C16	20
Net length	1.500 mm
Net width	300 mm
Net height	20 mm
Weight	6,0 kg

Light Engine Data

Light Engine	Color temperature	Rated light current	Power supply value Typ	Luminous efficacy
Level 1	3000 K	5600 lm	46,00 W	122 lm/W
Level 2	4000 K	6000 lm	46,00 W	130 lm/W

For more sustainability in day-to-day business

New
packing



CO₂ OPTIMISED



NO PLASTIC



ONLY ONE MATERIAL



100% RECYCLABLE



www.trilux-twenty3.com/eco