



TRILUX
SIMPLIFY YOUR LIGHT.



ENVIRONMENTAL PRODUCT DECLARATION

PRODUCT ENVIRONMENTAL PROFILE - B.VEO TRACK

Reference product: BV G2 3PTD RF-FL 40-EW C41 BLE 05

Registration number	TRLX-00031-V01.01-EN	Drafting rules	PCR-ed-EN-2021 09 06
		Supplemented by	PSR-0014-ed2.0-EN2023 07 13
Verifier accreditation number	VH45	Information and reference documents	www.pep-ecopassport.org
Date of issue	02-2026	Validity period	5 years

Independent verification of the declaration and data, in compliance with ISO 14025: 2006.

Internal	External	X
-----------------	-----------------	---

The PCR review was conducted by a panel of experts chaired by Julie Orgelet (DDemain).

PEPs are compliant with XP C08-100-1:2016 or EN 50693:2019.

The components of the present PEP may not be compared with components from any other program.

Document complies with ISO 14025:2006 „Environmental labels and declarations. Type III environmental declarations“.

Company information:

Further technical information can be obtained by contacting:
TRILUX GmbH & Co. KG, Heidestraße 4, D-59759 Arnsberg, Germany
or on the website www.trilux.com
or by email support@trilux.com

1. GENERAL INFORMATION

1.1 Product information

Track spotlight with discreetly reduced luminaire design in small construction. Can be swivelled through 90° and rotated through 355°. With CASAMBI module for integration into a wirelessly controllable mesh network of up to 250 devices. The system is commissioned using the Casambi app (iOS and Android). Radio range of the radio module under ideal conditions: 25,0 m. The radio range can vary depending on the influencing factors in the environment (e.g. walls, ceilings, floors, machines, steel beams, live cables). The radio range can be increased by using an additional radio module as a repeater. Mounting to 3-phase track in accordance with DIN EN 60570 via integrated 3-phase track adapter. For integration in Nordic-Global track. Optical system with 3-D faceted reflector. Flood distribution characteristic. beam angle 37°. Luminaire luminous flux and light color fixed. Luminaire luminous flux 3695 lm, connected load 29 W, Light colour warm white, correlated colour temperature (CCT) 3200 K Efficient White, general colour rendering index (CRI) R_a > 90. Colour locus tolerance (initial MacAdam) ? 2 SDCM. Mean rated service life L80 (t_q 25 °C) = 50,000 h. Flicker: Pst LM ? 1.0 at full load. Stroboscopic effect: SVM ? 0.4 at full load. Luminaire body of die-cast aluminium. Surface coated black (similar to RAL 9005). Luminaire dimensions (L x W x H): 255 mm x 91 mm x 151 mm. Safety class (EN 61140): II, protection rating (DIN EN 60529): IP20. Permissible ambient temperature (t_a): 25 °C Weight: 0,8 kg. The driver is integrated in the track adapter. The rated operating voltage of the luminaire is 230 V, 50/60 Hz. With Bluetooth Low Energy (BLE) control gear unit. The luminaire complies with the fundamental requirements of applicable EU regulations and product safety legislation and bears the CE symbol.

1. GENERAL INFORMATION

Table 1: Key technological data

Information	Unit	
Light source	-	Integrated LED module
Power supply	-	Integrated power supply
Color temperature	K	3,200
Protection index for water and dust (IP)	-	IP20
Impact resistance index (IK)	-	IK00
Nominal operating voltage	V	220-240
Declared lifetime of the luminaire	hr	50,000
Outgoing luminous flux/Useful output flux	lm	3,695
Electrical input power	W	29
Luminous efficiency	lm/W	127
Dimension	mm	255 x 151 x 91
Reference use scenario	-	Retail
Lifetime in years according to reference use scenario	yr	10

1.2 Goal and Scope

Following information has been used to generate the PEP:

Table 2: Goal and Scope

Information	
Functional unit	Provide lighting that delivers an outgoing artificial luminous flux of 1,000 lumens during a reference lifetime of 35,000 hours
Reference flow / declared unit*	0.1894 pieces of product
Life cycle stages covered	Cradle-to-grave and Module D
Product category according to PSR	Luminaires
Product family name	B.Veo Track
Product name	BV G2 3PTD RF-FL 40-EW C41 BLE 05
All products of the product family ["X" refer to placeholders for different product codes]	Please find a full list of aliases on Table 12 within this document.
*The reference flow is calculated as: $(1,000/\text{outgoing luminous flux of the analyzed product in lumens}) \times (35,000/\text{declared product lifetime of the analyzed product in hours})$. Consequently, the reference flow of the following product correspond to: $(1,000/3,695) \times (35,000/50,000) = 0.1894$	

2. CONSTITUENT MATERIALS

2.1 Overview

The product composition is shown in the following table.

Table 3: Product composition

	Weight [in kg]	Share [in %]
Total Weight	0.950	100
Product	0.835	88
Packaging	0.115	12

2.2 Product

The material composition of the product is shown in the following table.

Table 4: Material composition - product

	Weight [in kg]	Share [in %]
Total weight	0.835	100
Metals	0.640	77
Aluminium	0.631	76
Steel	0.007	1
Stainless Steel	0.002	0
Copper	0.000	0
Plastics	0.020	2
Acrylonitrile butadiene styrene (ABS)	0.000	0
Poly Vinyl Chloride (PVC)	0.003	0
Polyamide (PA)	0.000	0
Ethylene Propylene Diene Monomer (EPDM)	0.000	0
Polycarbonate/Polybutylene terephthalate (PC/PBT) blend	0.007	1
Polycarbonate (PC)	0.008	1
Polycarbonate/Acrylonitrile butadiene styrene (PC/ABS) blend	0.000	0
Polymethyl Methacrylate (PMMA)	0.000	0
Polyurethane (PU)	0.000	0
Silicone	0.001	0
Polyethylene (PE)	0.000	0
Graphite	0.001	0
Other	0.175	21
Electronics	0.175	21
Batteries	0.000	0
Glass	0.000	0
Paint	0.000	0

2.3 Packaging

The product composition is shown in the following table.

Table 5: Material composition - packaging

	Weight [in kg]	Share [in %]
Total weight	0.115	100
Paper/Cardboard	0.115	100
Plastic	0.000	0
Wood	0.000	0

3. INFORMATION ON LIFE CYCLE STAGES



3.1 Manufacturing stage (A1-A3)

The manufacturer sources all parts from different suppliers. The production site is in China/Germany . During the production is no energy or material input is required. Material were modelled with a global process from ecoinvent 3.9.1. Further, transport distances for materials were calculated according to PEP-PCR-ed4- EN-2021 09 06 since no specific data regarding transport were available. Ship: 19,000 km, Lorry: 1,000 km. A basic assumption in accordance with PSR-0014-ed2.0-EN-2023 07 13 was used to model the waste streams of the packaging for the raw materials. According to the PSR 5% of the luminaire's mass shall be considered as packaging (14,9 kg*0,05= 0,745 kg). The packaging materials shall then be split as follows: Wood: 50% (0,3725 kg), Cardboard: 40 % (0,298 kg), LDPE:10 % (0,0745 kg). Further, transportation from the production site to storage site was modeled with 78 km according to the information given by the supplier. Also, to produce the luminaire a marginal sum of electricity was used which was cut-off. Additionally, for production of the luminaire only recyclable waste from cardboard was generated with transportation to the location of the end-of-life-stage of 10 km according to manufacturer specific data.



3.2 Distribution stage (A4)

The main market of the product is Europe and there is no specific data available. For this reason, an intracontinental transport (3,500 km by truck (diesel driven, EURO 0-6, >27t payload) to the place of use following PEP-PCR-ed4-EN-2021 09 06 is considered.



3.3 Installation stage (A5)

The product can easily be installed without any special tool. No energy or material input is required. Packaging waste is treated according to the scenario given in PEP-PSR-0014-ed2-EN-2023 07 13 by PEP ecopassport.



3.4 Use stage (B1-B7)

The product has no direct emissions (B1). No maintenance (B2), repair (B3), replacement (B4), or refurbishment (B5) is required. The use of the product does consume electricity (B6), but no water (B7).

The operational electricity consumption over the entire lifetime of the product is 1,45 kWh. It has been calculated according to PSR edition 2. The used energy model refers to an average European electricity grid mix from Sphera's Managed LCA Content.



3.5 End-of-life stage (C1-C4)

The product falls under the Waste from Electrical and Electronic Equipment (WEEE) directive 2012/19/ EU. Therefore, a collection rate of 100% and a typical end-of-life scenario for electronic products is assumed. All (mechanical and electronic) metals are recycled. Plastic & renewable materials are incinerated with energy recovery. Batteries & glass are landfilled. For the transport to end-of-life treatment 1,000 km by truck according to PEP PCR is considered.

3.6 Benefits and loads beyond the system boundaries stage (D)

The recycling of the product (incl. packaging) and incineration with energy recovery generates environmental benefits and loads beyond the system boundaries (D). The calculation of this module is in line with the formulars described in PEP-PCR-ed4-EN-2021 09 06. The amount of the material flows used for the calculation are listed in the table below.

Table 6: Material flows for benefits and loads beyond the system boundaries per functional unit

	Weight [in kg]
Total weight going into incineration with energy recovery	0.190
Total weight going into recycling	0.644

4. ENVIRONMENTAL INFORMATION

The environmental information included in this study cover all stages of the life cycle („cradle-to-grave“).

The life cycle is divided into manufacturing stage (A1-A3), distribution stage (A4), installation stage (A5), use stage (B1-B7, but only applicable modules are shown), End-of-life stage (C1-C4) and benefits and loads beyond the system boundaries (D). The results refer to the core environmental impact indicators and mandatory indicators describing resource use, waste categories, and output flows according to PEP-PCR-ed4, - EN-2021 09 06 and EN 15804+A2:2019.

The results have been calculated using the LCA Software “LCA for Experts 10” and the LCI database “Sphera Managed LCA Content”.

4.1 Results per functional unit

The following results of the environmental declaration have been developed, considering an outgoing artificial luminous flux of 1,000 lumens over a reference lifetime of 35,000 hours.

Acronyms: GWP-total=Global Warming Potential total; GWP-biogenic=Global Warming Potential biogenic; GWP-fossil=Global Warming Potential fossil; GWP-luluc=Global Warming Potential land use and land use change; ODP=Ozone Depletion; AP=Acidification; EP=Eutrophication; POCP=Photochemical ozone formation; ADPE=Depletion of abiotic resources-minerals and metals; ADPF=Depletion of abiotic resources-fossil fuels; WDP=Water resource depletion; PERE=Renewable primary energy (without raw material); PERM=Renewable primary energy (raw material); PERT=Total use of renewable primary energy; PENRE=Non-renewable primary energy (without raw material); PENRM=Non-renewable primary energy (raw material); PENRT=Total use of non-renewable primary energy; SM=Use of secondary materials; RSF=Use of renewable secondary fuels; NRSF=Use of non-renewable secondary fuels; FW=Net use of fresh water; HWD=Hazardous waste disposed; NHWD=Non-hazardous waste disposed; RWD=Radioactive waste disposed; CRU=Components for reuse; MFR=Materials for recycling; MER=Materials for energy recovery; EEE=Exported electricity; EET=Exported thermal energy; Biog. C in product=Biogenic carbon content of the product; Biog. C in packaging=Biogenic carbon content of the associated packaging

4. ENVIRONMENTAL INFORMATION

Table 7: Results core environmental impact indicators per functional unit

Impact category	Unit	Total (excl. D)	Manufacturing			Distribution	Installation
			A1	A2	A3		
GWP - total	kg CO2 eq.	4.73E+01	3.09E+00	1.65E-02	1.20E-01	5.05E-02	1.85E-02
GWP - fossil	kg CO2 eq.	4.67E+01	3.09E+00	1.58E-02	1.06E-01	4.97E-02	1.22E-02
GWP - biogenic	kg CO2 eq.	4.66E-01	-8.94E-04	5.78E-04	1.32E-02	7.20E-04	6.26E-03
GWP - luluc	kg CO2 eq.	1.51E-01	7.11E-03	1.16E-04	3.22E-04	1.39E-04	5.39E-05
ODP	kg CFC-11 eq.	1.01E-09	1.99E-11	2.31E-15	5.97E-13	5.67E-15	2.87E-14
AP	Mole of H+ eq.	1.11E-01	1.43E-02	1.23E-04	2.01E-04	8.19E-04	3.08E-05
EP - freshwater	kg P eq.	1.02E-04	7.67E-06	3.14E-08	1.58E-06	4.54E-08	2.46E-07
EP - marine	kg N eq.	2.60E-02	2.72E-03	4.52E-05	8.96E-05	2.94E-04	1.62E-05
EP- terrestrial	Mole of N eq.	2.88E-01	2.76E-02	4.93E-04	8.61E-04	3.22E-03	1.39E-04
POCP	kg NMVOC eq.	6.54E-02	7.64E-03	1.20E-04	1.85E-04	8.09E-04	2.56E-05
ADPE	kg Sb eq.	1.21E-04	1.12E-04	8.64E-10	2.23E-08	1.80E-09	7.53E-09
ADPF	MJ	9.20E+02	3.26E+01	1.99E-01	1.24E+00	5.99E-01	1.64E-01
WDP	m³ world equiv.	1.16E+01	7.51E-01	6.01E-05	8.17E-03	1.29E-04	1.46E-03

Impact category	Unit	Use		End of life			Benefits*
		B2	B6	C2	C3	C4	
GWP - total	kg CO2 eq.	0.00E+00	4.40E+01	1.23E-02	3.68E-02	9.01E-06	-1.06E+00
GWP - fossil	kg CO2 eq.	0.00E+00	4.34E+01	1.16E-02	3.68E-02	8.69E-06	-1.07E+00
GWP - biogenic	kg CO2 eq.	0.00E+00	4.46E-01	6.00E-04	4.40E-05	2.85E-07	2.01E-02
GWP - luluc	kg CO2 eq.	0.00E+00	1.43E-01	1.21E-04	2.09E-05	3.56E-08	-2.65E-03
ODP	kg CFC-11 eq.	0.00E+00	9.88E-10	1.95E-15	1.12E-13	2.42E-17	-1.68E-11
AP	Mole of H+ eq.	0.00E+00	9.50E-02	2.11E-05	2.92E-05	6.14E-08	-4.20E-03
EP - freshwater	kg P eq.	0.00E+00	9.28E-05	3.16E-08	1.39E-08	1.29E-11	-1.07E-06
EP - marine	kg N eq.	0.00E+00	2.28E-02	8.97E-06	1.10E-05	1.61E-08	-9.36E-04
EP- terrestrial	Mole of N eq.	0.00E+00	2.55E-01	9.56E-05	1.31E-04	1.75E-07	-1.02E-02
POCP	kg NMVOC eq.	0.00E+00	5.66E-02	1.90E-05	2.81E-05	4.81E-08	-2.67E-03
ADPE	kg Sb eq.	0.00E+00	9.02E-06	7.80E-10	1.04E-09	5.38E-13	-1.52E-05
ADPF	MJ	0.00E+00	8.85E+02	1.50E-01	1.14E-01	1.14E-04	-1.34E+01
WDP	m³ world equiv.	0.00E+00	1.09E+01	5.37E-05	7.06E-03	9.40E-07	-1.10E-01

*Benefits and loads beyond the system boundaries

4. ENVIRONMENTAL INFORMATION

Table 8: Results indicators describing resource use, waste categories, and output flows per functional unit

Impact category	Unit	Total (excl. D)	Manufacturing			Distribution	Installation
			A1	A2	A3	A4	A5
PERE	MJ	6.14E+02	8.71E+00	1.11E-02	2.70E-01	1.50E-02	7.69E-02
PERM	MJ	4.24E-01	1.21E-01	0.00E+00	3.36E-01	0.00E+00	-3.25E-02
PERT	MJ	6.15E+02	8.83E+00	1.11E-02	6.06E-01	1.50E-02	4.44E-02
PENRE	MJ	9.20E+02	3.25E+01	1.99E-01	1.25E+00	5.99E-01	1.64E-01
PENRM	MJ	1.83E-02	1.34E-01	0.00E+00	-1.29E-02	0.00E+00	0.00E+00
PENRT	MJ	9.20E+02	3.26E+01	1.99E-01	1.24E+00	5.99E-01	1.64E-01
SM	kg	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
FW	m3	4.90E-01	1.98E-02	5.69E-06	4.24E-04	8.99E-06	9.77E-05
HWD	kg	1.27E-06	2.70E-08	7.68E-12	6.68E-09	2.17E-11	2.42E-09
NHWD	kg	1.27E+00	5.35E-01	2.45E-05	4.09E-02	5.84E-05	1.91E-03
RWD	kg	1.41E-01	8.17E-04	3.37E-07	2.21E-05	8.30E-07	3.90E-06
MFR	kg	1.46E-01	0.00E+00	0.00E+00	5.81E-03	0.00E+00	1.79E-02
MER	kg	5.97E-02	0.00E+00	0.00E+00	2.18E-02	0.00E+00	1.96E-03
EEE	MJ	5.93E-02	3.84E-04	0.00E+00	0.00E+00	0.00E+00	5.01E-03
EET	MJ	1.34E-01	6.86E-04	0.00E+00	0.00E+00	0.00E+00	7.63E-03
Biog. C in packa- ging	kg	1.17E+00	3.06E-01	0.00E+00	8.62E-01	0.00E+00	0.00E+00

Impact category	Unit	Use		End of life			Benefits*
		B2	B6	C2	C3	C4	D
PERE	MJ	0.00E+00	6.05E+02	1.13E-02	6.98E-02	2.20E-05	-9.03E+00
PERM	MJ	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
PERT	MJ	0.00E+00	6.05E+02	1.13E-02	6.98E-02	2.20E-05	-9.03E+00
PENRE	MJ	0.00E+00	8.85E+02	1.50E-01	2.17E-01	1.14E-04	-1.34E+01
PENRM	MJ	0.00E+00	0.00E+00	0.00E+00	-1.03E-01	0.00E+00	0.00E+00
PENRT	MJ	0.00E+00	8.85E+02	1.50E-01	1.14E-01	1.14E-04	-1.34E+01
SM	kg	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	1.17E-01
FW	m3	0.00E+00	4.70E-01	5.60E-06	1.88E-04	2.75E-08	-5.40E-03
HWD	kg	0.00E+00	1.23E-06	6.03E-12	5.43E-10	2.49E-14	-1.27E-08
NHWD	kg	0.00E+00	6.86E-01	2.10E-05	6.29E-03	5.69E-04	-3.19E-01
RWD	kg	0.00E+00	1.40E-01	2.84E-07	1.48E-05	1.21E-09	-7.18E-04
MFR	kg	0.00E+00	0.00E+00	0.00E+00	1.22E-01	0.00E+00	0.00E+00
MER	kg	0.00E+00	0.00E+00	0.00E+00	3.59E-02	0.00E+00	0.00E+00
EEE	MJ	0.00E+00	0.00E+00	0.00E+00	5.39E-02	0.00E+00	0.00E+00
EET	MJ	0.00E+00	0.00E+00	0.00E+00	1.25E-01	0.00E+00	0.00E+00
Biog. C in packa- ging	kg	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00

*Benefits and loads beyond the system boundaries

4. ENVIRONMENTAL INFORMATION

4.2 Results per unit of product

The following results of the environmental declaration have been developed, considering one piece of product.

Table 9: Results core environmental impact indicators per unit of product

Impact category	Unit	Total (excl. D)	Manufacturing			Distribution	Installation
			A1	A2	A3	A4	A5
GWP - total	kg CO2 eq.	2.50E+02	1.63E+01	8.69E-02	6.32E-01	2.67E-01	9.75E-02
GWP - fossil	kg CO2 eq.	2.46E+02	1.63E+01	8.32E-02	5.61E-01	2.62E-01	6.42E-02
GWP - biogenic	kg CO2 eq.	2.46E+00	-4.72E-03	3.05E-03	6.95E-02	3.80E-03	3.30E-02
GWP - luluc	kg CO2 eq.	7.97E-01	3.75E-02	6.10E-04	1.70E-03	7.32E-04	2.84E-04
ODP	kg CFC-11 eq.	5.33E-09	1.05E-10	1.22E-14	3.15E-12	2.99E-14	1.51E-13
AP	Mole of H+ eq.	5.83E-01	7.54E-02	6.48E-04	1.06E-03	4.32E-03	1.63E-04
EP - freshwater	kg P eq.	5.40E-04	4.05E-05	1.66E-07	8.34E-06	2.39E-07	1.30E-06
EP - marine	kg N eq.	1.37E-01	1.44E-02	2.39E-04	4.73E-04	1.55E-03	8.53E-05
EP- terrestrial	Mole of N eq.	1.52E+00	1.45E-01	2.60E-03	4.55E-03	1.70E-02	7.34E-04
POCP	kg NMVOC eq.	3.45E-01	4.03E-02	6.32E-04	9.77E-04	4.27E-03	1.35E-04
ADPE	kg Sb eq.	6.39E-04	5.91E-04	4.56E-09	1.18E-07	9.52E-09	3.97E-08
ADPF	MJ	4.86E+03	1.72E+02	1.05E+00	6.54E+00	3.16E+00	8.64E-01
WDP	m³ world equiv.	6.15E+01	3.97E+00	3.17E-04	4.31E-02	6.82E-04	7.68E-03

Impact category	Unit	Use		End of life			Benefits*
		B2	B6	C2	C3	C4	D
GWP - total	kg CO2 eq.	0.00E+00	2.32E+02	6.49E-02	1.94E-01	4.75E-05	-5.58E+00
GWP - fossil	kg CO2 eq.	0.00E+00	2.29E+02	6.11E-02	1.94E-01	4.59E-05	-5.67E+00
GWP - biogenic	kg CO2 eq.	0.00E+00	2.35E+00	3.17E-03	2.32E-04	1.50E-06	1.06E-01
GWP - luluc	kg CO2 eq.	0.00E+00	7.56E-01	6.38E-04	1.10E-04	1.88E-07	-1.40E-02
ODP	kg CFC-11 eq.	0.00E+00	5.22E-09	1.03E-14	5.92E-13	1.28E-16	-8.86E-11
AP	Mole of H+ eq.	0.00E+00	5.02E-01	1.11E-04	1.54E-04	3.24E-07	-2.22E-02
EP - freshwater	kg P eq.	0.00E+00	4.90E-04	1.67E-07	7.36E-08	6.82E-11	-5.63E-06
EP - marine	kg N eq.	0.00E+00	1.20E-01	4.73E-05	5.79E-05	8.48E-08	-4.94E-03
EP- terrestrial	Mole of N eq.	0.00E+00	1.35E+00	5.05E-04	6.92E-04	9.25E-07	-5.39E-02
POCP	kg NMVOC eq.	0.00E+00	2.99E-01	1.00E-04	1.48E-04	2.54E-07	-1.41E-02
ADPE	kg Sb eq.	0.00E+00	4.76E-05	4.12E-09	5.48E-09	2.84E-12	-8.01E-05
ADPF	MJ	0.00E+00	4.67E+03	7.94E-01	6.02E-01	6.02E-04	-7.06E+01
WDP	m³ world equiv.	0.00E+00	5.74E+01	2.83E-04	3.72E-02	4.96E-06	-5.79E-01

*Benefits and loads beyond the system boundaries

4. ENVIRONMENTAL INFORMATION

Table 10: Results indicators describing resource use, waste categories, and output flows per unit of product

Impact category	Unit	Total (excl. D)	Manufacturing			Distribution	Installation
			A1	A2	A3	A4	A5
PERE	MJ	3.24E+03	4.60E+01	5.86E-02	1.43E+00	7.93E-02	4.06E-01
PERM	MJ	2.24E+00	6.36E-01	0.00E+00	1.77E+00	0.00E+00	-1.71E-01
PERT	MJ	3.24E+03	4.66E+01	5.86E-02	3.20E+00	7.93E-02	2.34E-01
PENRE	MJ	4.86E+03	1.71E+02	1.05E+00	6.61E+00	3.16E+00	8.64E-01
PENRM	MJ	9.66E-02	7.10E-01	0.00E+00	-6.81E-02	0.00E+00	0.00E+00
PENRT	MJ	4.86E+03	1.72E+02	1.05E+00	6.54E+00	3.16E+00	8.64E-01
SM	kg	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
FW	m3	2.59E+00	1.04E-01	3.00E-05	2.24E-03	4.75E-05	5.16E-04
HWD	kg	6.68E-06	1.42E-07	4.05E-11	3.53E-08	1.15E-10	1.28E-08
NHWD	kg	6.71E+00	2.82E+00	1.29E-04	2.16E-01	3.08E-04	1.01E-02
RWD	kg	7.42E-01	4.31E-03	1.78E-06	1.17E-04	4.38E-06	2.06E-05
MFR	kg	7.69E-01	0.00E+00	0.00E+00	3.07E-02	0.00E+00	9.43E-02
MER	kg	3.15E-01	0.00E+00	0.00E+00	1.15E-01	0.00E+00	1.04E-02
EEE	MJ	3.13E-01	2.03E-03	0.00E+00	0.00E+00	0.00E+00	2.64E-02
EET	MJ	7.06E-01	3.62E-03	0.00E+00	0.00E+00	0.00E+00	4.03E-02
Biog. C in packa- ging	kg	6.16E+00	1.61E+00	0.00E+00	4.55E+00	0.00E+00	0.00E+00

Impact category	Unit	Use		End of life			Benefits*
		B2	B6	C2	C3	C4	D
PERE	MJ	0.00E+00	3.19E+03	5.98E-02	3.68E-01	1.16E-04	-4.76E+01
PERM	MJ	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
PERT	MJ	0.00E+00	3.19E+03	5.98E-02	3.68E-01	1.16E-04	-4.76E+01
PENRE	MJ	0.00E+00	4.67E+03	7.94E-01	1.15E+00	6.02E-04	-7.06E+01
PENRM	MJ	0.00E+00	0.00E+00	0.00E+00	-5.45E-01	0.00E+00	0.00E+00
PENRT	MJ	0.00E+00	4.67E+03	7.94E-01	6.02E-01	6.02E-04	-7.06E+01
SM	kg	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	6.18E-01
FW	m3	0.00E+00	2.48E+00	2.96E-05	9.94E-04	1.45E-07	-2.85E-02
HWD	kg	0.00E+00	6.49E-06	3.18E-11	2.87E-09	1.32E-13	-6.72E-08
NHWD	kg	0.00E+00	3.62E+00	1.11E-04	3.32E-02	3.00E-03	-1.68E+00
RWD	kg	0.00E+00	7.37E-01	1.50E-06	7.81E-05	6.39E-09	-3.79E-03
MFR	kg	0.00E+00	0.00E+00	0.00E+00	6.44E-01	0.00E+00	0.00E+00
MER	kg	0.00E+00	0.00E+00	0.00E+00	1.90E-01	0.00E+00	0.00E+00
EEE	MJ	0.00E+00	0.00E+00	0.00E+00	2.85E-01	0.00E+00	0.00E+00
EET	MJ	0.00E+00	0.00E+00	0.00E+00	6.62E-01	0.00E+00	0.00E+00
Biog. C in packa- ging	kg	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00

*Benefits and loads beyond the system boundaries

5. EXTRAPOLATION RULE FOR PRODUCT VARIANTS

5.1 Extrapolation coefficients

The extrapolation coefficients included in the PEP have been developed according to the valid PCR & PSR. The table below shows the key properties of the reference product, function as extrapolation basis.

Table 11: Reference values for the extrapolation

Export Tabelle mit textlicher Formatierung		
Parameter	Unit	Value
Weight of structural/mechanical parts	kg	0.684
Weight of power equipment	kg	0.15
Weight of light source	kg	0.001
Weight of light management system	kg	0
Weight of product (excl. packaging)	kg	0.835
Weight of packaging	kg	0.115
Typical power consumption	W	29
Lumen output	lm	3695
Energy saving coefficient	-	0.5

The extrapolation at the level of the functional unit needs to be done according to the following formula:

$$\text{Extrapolation coefficient at the product level} \times \left(\frac{\text{Lighting output of reference product (lumens)}}{\text{Lighting output of concerned product (lumens)}} \right)$$

The required extrapolation coefficients at the product level are listed in the following table. The Lighting output should be taken from the datasheet of the individual variant (value of phi).

Table 12: Extrapolation coefficients at the product level

Product variant	Fabrication stage	Distribution stage	Installation stage	Use stage	End of life stage
BV G2 3PTD RF-XX(X) XX -XX CXX BLE XX	1.00	1.00	1.00	1.00 x P in datasheet / 29 W	1.00
BV G2 3PTD RF-XX(X) XX -XX CXX ET XX	0.99	0.99	0.99	2.00 x P in datasheet / 29 W	0.99
BV G2 3PTD RF-XX(X) XX -XX CXX ETDD XX	1.00	1.00	1.00	1.00 x P in datasheet / 29 W	1.00
BV G2 3PTD RF-XX(X) XX-M(+F) CXX BLE XX	1.00	1.00	1.00	1.00 x P in datasheet / 29 W	1.00
BV G2 3PTD RF-XX(X) XX-M(+F) CXX ET XX	0.99	0.99	0.99	2.00 x P in datasheet / 29 W	0.99
BV G2 3PTD RF-XX(X) XX-M(+F) CXX ETDD XX	1.00	1.00	1.00	1.00 x P in datasheet / 29 W	1.00
BV G2 3PTD RF-XX(X) XX-XXX CXX BLE XX	1.00	1.00	1.00	1.00 x P in datasheet / 29 W	1.00
BV G2 3PTD RF-XX(X) XX-XXX CXX ET XX	0.99	0.99	0.99	2.00 x P in datasheet / 29 W	0.99
BV G2 3PTD RF-XX(X) XX-XXX CXX ETDD XX	1.00	1.00	1.00	1.00 x P in datasheet / 29 W	1.00
BV G2 3PTD RF-XX(X)-c XX -XX CXX BLE XX	1.04	1.04	1.00	1.00 x P in datasheet / 29 W	1.04
BV G2 3PTD RF-XX(X)-c XX -XX CXX ET XX	1.03	1.03	0.99	2.00 x P in datasheet / 29 W	1.03
BV G2 3PTD RF-XX(X)-c XX -XX CXX ETDD XX	1.04	1.04	1.00	1.00 x P in datasheet / 29 W	1.04
BV G2 3PTD RF-XX(X)-c XX-M(+F) CXX BLE XX	1.04	1.04	1.00	1.00 x P in datasheet / 29 W	1.04
BV G2 3PTD RF-XX(X)-c XX-M(+F) CXX ET XX	1.03	1.03	0.99	2.00 x P in datasheet / 29 W	1.03
BV G2 3PTD RF-XX(X)-c XX-M(+F) CXX ETDD XX	1.04	1.04	1.00	1.00 x P in datasheet / 29 W	1.04
BV G2 3PTD RF-XX(X)-c XX-XXX CXX BLE XX	1.04	1.04	1.00	1.00 x P in datasheet / 29 W	1.04
BV G2 3PTD RF-XX(X)-c XX-XXX CXX ET XX	1.03	1.03	0.99	2.00 x P in datasheet / 29 W	1.03
BV G2 3PTD RF-XX(X)-c XX-XXX CXX ETDD XX	1.04	1.04	1.00	1.00 x P in datasheet / 29 W	1.04

Legal Disclaimer

The information contained in this document is provided for general information purposes only and represents a standard-based environmental declaration derived from the assumptions, data and methodologies defined by the applicable standards, product category rules (PCR) and specific product rules (PSR) described herein. It does not constitute a guarantee or warranty of specific product properties, nor does it form part of any contractual agreement. The characteristics of products are binding only if expressly agreed in the relevant contract.

While TRILUX has taken reasonable care to ensure the accuracy of the data, no representation or warranty is given, either express or implied, regarding the completeness, accuracy or fitness for a particular purpose of the information provided.

The values and results stated in this EPD are valid only within the defined scope, system boundaries and assumptions. They are not intended to be used as the sole basis for environmental assessments of installations or buildings and may not be directly comparable with data from EPDs based on different standards or product category rules. TRILUX shall not be liable for any damages or consequences arising from the use or interpretation of the information contained in this document, except in cases of mandatory liability under applicable law.

Subject to technical modifications and errors.

All product names and trademarks mentioned are the property of their respective owners.