



2330 G3 M73 PW19 3600-8MC ETDD

Recessed LED luminaire

TOC: 7798651



Product description

Luminaire type

Square recessed LED ceiling luminaire with prismatic PMMA cover. Version M73 (600 mm x 600mm).

Applications

Offices, Corridors, Foyers, Conference rooms, Retail areas, waiting zones.

Mounting methods

For system ceilings with exposed grids.

Optical system

PMMA cover with microprisms. With symmetric limited wide light distribution. beam angle 81°. Glare evaluation according to UGR rating (EN 12464-1) < 19. Suitable for VDU workstations according to EN 12464-1 via limited luminance $L \leq 3000 \text{ cd/m}^2$ for beam angle above 65° all-round. Harmonious light effect due to homogeneously illuminated light emission.

LED system

Light color adjustable in 2 steps (Multilumen). Luminaire luminous flux 3600 lm, connected load 31 W, Power Faktor $\lambda > 0,9$, maximum luminous efficiency of luminaire 116 lm/W. Light colour warm white or neutral white, correlated colour temperature (CCT) 3000 K or 4000 K, general colour rendering index (CRI) $R_a > 80$. Colour locus tolerance (initial MacAdam) $\leq 5 \text{ SDCM}$. Mean rated service life $L70 (t_q 25^\circ\text{C}) = 50,000 \text{ h}$.

Luminaire body

Luminaire body of aluminium. Surface coated white (similar to RAL 9016). Dimensions (L x W): 595 mm x 595 mm, luminaire height 69 mm. Safety class (EN 61140): I, protection rating (DIN EN 60529): IP20, Protection rating on room side: IP40, impact resistance level in accordance with IEC 62262: IK02, testing temperature of wire glow test in accordance with IEC 60695-2-11: 650 °C. Permissible ambient temperature (t_a): 25 °C. Weight: 2,0 kg.

Electrical version

With electronic control gear unit, digitally dimmable (DALI). Control gear unit according to DALI-2 standard (EN 62386). Luminaire is switchable and dimmable by means of touch functionality via DALI control terminals (Touch DIM). The control gear unit is replaceable in accordance with the ecodesign requirements (VO (EU) 2019/2020). The luminaire complies with the fundamental requirements of applicable EU regulations and product safety legislation and bears the CE symbol. The luminaire is also ENEC-certified by an independent testing authority.

Disassembly instructions (PDF) for the product available at: <https://www.trilux.com/EcoDesign>

Product features and key data

Applications	Offices Corridors Foyers Conference rooms Sales rooms Waiting zones	
Luminaire type	Square recessed LED ceiling luminaire with prismatic PMMA cover.	
Mounting method	Recessed	
Luminaire optic	PMMA cover with microprisms.	
Light distribution curve	Wide reduced glare UGR19 (W19)	
FWHM	80,60 °	
Light Engine	Level 2	Level 1
Colour temperature	3000 K	4000 K
Rated luminous flux	3400 lm	3600 lm
Connected load	31,00 W	31,00 W

Product features and key data

Luminous efficacy	110 lm/W	116 lm/W
Rated service life	L70 (25 °C) = 50.000 h	
Colour rendering index	80	
Colour tolerance	5 SDCM	
Photobiological class	Group 0 - no risk	
Luminaire colour	RAL9016 Traffic white	
Luminaire body	Luminaire body of aluminium.	
Electrical version	With electronic control gear unit, digitally dimmable (DALI).	
DALI-2-Standard EN 62386	Yes	
Wire diameter	1,50 mm²	
Connection method	Plug-in terminal	
Touch-Dim-capable	Yes	
Number of DALI addresses	1	
Dimming range	5 - 100 %	
Mains voltage	220 - 240 V	
Mains frequency	50/60 Hz	
Total harmonic distortion < %	14 %	
Ingress Protection (IP) rating	IP20	
Protection rating on room side	IP40	
Protection class	I	
Impact resistance (IK)	IK02	
Hot wire resistance	650 °C	
Ambient temperature	25 °C	
Max. Luminaires B10	31	
Max. Luminaires B16	50	
Max. Luminaires C10	52	
Max. Luminaires C16	85	
Net length	595 mm	
Net width	595 mm	
Net height	69 mm	
Recess length	595 mm	
Recess width	595 mm	
Recess depth	190 mm	
Weight	2,0 kg	

Available accessories

Material	Description
7716400	Suspension accessories for luminaires of the series: 2330...G3 .

Light Engine Data

Light Engine	Color temperature	Rated light current	Power supply value Type	Luminous efficacy
Level 2	3000 K	3400 lm	31,00 W	110 lm/W
Level 1	4000 K	3600 lm	31,00 W	116 lm/W

EPREL - European Product Registry for Energy Labelling

Energy Efficiency Class	Model identifier
D	S10250055

For more sustainability in day-to-day business

New
packing



CO₂ OPTIMISED



NO PLASTIC



ONLY ONE MATERIAL



100% RECYCLABLE



www.trilux-twenty3.com/eco